

Product High Foam Traffic Film Remover
 Revision date 29 May 2020
 Revision 3



Safety Data Sheet (SDS)
 according to Regulation (EC) No. 1907/2006

Section 1: Identification of the substance/preparation and of the company/undertaking

1.1 Product identifier

Product name	High Foam Traffic Film Remover
Product no.	INDHFTFRS
Synonyms, Trade names	No information available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Cleaning agent.
Uses advised against	Any other purpose.

1.3 Details of the supplier of the safety data sheet

Supplier	Kitchenmaster NI Ltd 11 Comber Road Belfast BT8 8AN United Kingdom Tel: 028 90814777
Contact person	sales@kitchenmaster-ni.com

1.4 Emergency telephone number

Emergency telephone	Emergency Telephone Number: 028 9081 4777 08:30 - 17:00 Monday to Thursday 08:30 - 16:30 Friday
---------------------	---

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)	
Physical and chemical hazards	Not classified
Human health	Skin Corr. 1B - H314
Environment	Not classified

2.2 Label elements

Contains	disodium metasilicate sodium hydroxide caustic soda
Detergent labeling	<5% anionic surfactants <5% aliphatic hydrocarbons

Label in accordance with (EC) no. 1272/2008



Signal word	Danger
Hazard statements	H314 Causes severe skin burns and eye damage.
Precautionary statements	Prevention P260 Do not breathe dust/fume/ gas/mist/vapours/spray. P280 Wear protective gloves/ protective clothing/eye protection/face protection.

Response

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

2.3 Other hazards

None known.

Section 3: Composition/identification of ingredients**3.1 Substance**

Not applicable.

3.2 Mixtures

Name	Product identifier	Reg. EU 1272/2008	%
disodium metasilicate	CAS-No.: 6834-92-0 EC No.: 229-912-9	Skin Corr. 1B - H314, STOT SE 3 - H335	1-5%
Alcohols, C12-15, ethoxylated	CAS-No.: 68131-39-5 EC No.: 500-195-7	Skin Irrit. 2 - H315, Eye Dam. 1 - H318, Aquatic Acute 1 - H400	1-5%
propan-2-ol	CAS-No.: 67-63-0 EC No.: 200-661-7 REACH Reg No.: 01-2119457558-25-0000	Eye Irrit. 2A - H319, Flam. Liq 2- H225, STOT SE 3 - H336	0.1-0.9%
sodium hydroxide caustic soda	CAS-No.: 1310-73-2 EC No.: 215-185-5	Skin Corr. 1A - H314	0.1-0.9%
N,N-dimethyltetradecylamine N-oxide	CAS-No.: 3332-27-2 EC No.: 222-059-3	Acute Tox 4 - H302, Skin Irrit. 2 - H315, Eye Dam. 1 - H318, Aquatic Acute 1 - H400, Aquatic Chronic 2 - H411	0.1-0.9%

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.

Section 4: First aid measures**4.1 Description of first aid measures**

General information	Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor. Seek medical attention for all burns and eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue.
Inhalation	Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.
Ingestion	If this product is ingested, remove victim immediately from source of exposure. Rinse mouth thoroughly. Do not induce vomiting. Provide fresh air, warmth and rest. Get medical attention. Never give anything by mouth to an unconscious person.
Skin contact	Remove victim immediately from source of exposure. Wash the skin immediately with water. Remove contaminated clothing, shoes and jewelry and wash before reuse. Obtain medical attention if irritation persists or if blistering occurs.
Eye contact	Do not rub eye. If this product contacts the eyes, gently flush eyes with water for at least fifteen (15) minutes, lifting the upper and lower eyelids occasionally. Remove contact lenses if present and easy to do so. Avoid contaminating unaffected eye. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	No specific symptoms noted. Inhalation may cause respiratory irritation.
Ingestion	May cause chemical burns in mouth and throat. May cause severe internal injury.
Skin contact	Corrosive. Causes severe skin burns.
Eye contact	Extreme irritation of eyes and mucous membranes, including burning and tearing. Corrosive to eyes.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician	Treat symptomatically.
------------------------	------------------------

Section 5: Fire-fighting measures**5.1 Extinguishing media**

Extinguishing media	Use fire-extinguishing media appropriate for surrounding materials. This product is not flammable.
Unsuitable extinguishing media	High volume water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products	When heated, toxic and corrosive vapours/gases may be formed. During fire, toxic gases (CO, CO ₂) are formed. Nitrogen oxides (NO _x). Hydrogen cyanide (HCN).
Unusual fire & explosion hazards	On contact with aluminium or light alloys hydrogen gas may be evolved.
Specific hazards	Water used for fire extinguishing, which has been in contact with the product, may be corrosive.

5.3 Advice for firefighters

Special fire fighting procedures	If possible, fight fire from protected position. Avoid breathing fire vapours. Ventilate closed spaces before entering them. Containers close to fire should be removed immediately or cooled with water if safe to do so.
Protective equipment for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. Eliminate all sources of ignition. Avoid inhalation of vapours and contact with skin and eyes. In case of inadequate ventilation, use respiratory protection. Do not touch or walk through spilled material. If necessary evacuate surrounding areas.
For emergency responders	Follow safe handling advice and personal protective equipment recommendations for normal use of product.

6.2 Environmental precautions

Environmental precautions	Do not discharge onto the ground or into water courses.
---------------------------	---

6.3 Methods and material for containment and cleaning up

Spill clean up methods	Ventilate and evacuate the area. Eliminate all ignition sources. Stop leak if possible without risk. DO NOT touch spilled material! When dealing with a spillage, wear necessary protective equipment. Absorb spillage with non-combustible, inert absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container. Wash thoroughly after dealing with a spillage.
------------------------	--

6.4 Reference to other sections

Reference to other sections	See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.
-----------------------------	--

Section 7: Handling and storage**7.1 Precautions for safe handling**

Handling	Read and follow manufacturer's recommendations. Use proper personal protection when handling (refer to Section 8). Do not handle broken packages without protective equipment. Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Do not
----------	---

eat, drink or smoke when using the product. Wash thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Storage precautions	Keep upright, locked up and out of reach of children. Keep the product in its original container. Store in cool dry areas away from direct sunlight or sources of ignition.
Storage class	Corrosive storage.

7.3 Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
Usage description	Use only according to directions. Replace and tighten cap after use.

Section 8: Exposure controls/Personal protection

8.1 Control parameters

Component	STD	TWA (8 Hrs)		STEL (15mins)		Notes
propan-2-ol	OEL	200 ppm		400 ppm		Sk
propan-2-ol	WEL	400 ppm	999 mg/m ³	500 ppm	1250 mg/m ³	
sodium hydroxide caustic soda	OEL				2 mg/m ³	
sodium hydroxide caustic soda	WEL				2 mg/m ³	

Ingredient comments	WEL - Workplace Exposure Limits - EH40/2005 Workplace exposure limits. Ireland, Occupational Exposure Limits 2020.
---------------------	--

8.2 Exposure Controls

Protective equipment



Engineering measures	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.
Respiratory equipment	If ventilation is inadequate, suitable respiratory protection must be worn. EN 136/140/145/143/149. The specific respirator selected must be based on contamination levels found in the work place. Where risk assessment shows air-purifying respirators are appropriate a full face respirator conforming to EN143 should be used, and suitable respirator cartridges as a backup to engineering controls. Consult manufacturer for specific advice.
Hand protection	Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374) is recommended. (EU Directive 89/686/EEC). Gloves must be inspected prior to use. Suggested material: Butyl-rubber. Layer thickness: 0.11mm. Breakthrough time: >480 min. Consult manufacturer for advice. Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
Eye protection	Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).
Other protection	Wear appropriate clothing to prevent skin contact. The selected clothing must satisfy the European norm standard EN 943. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Work clothing worn by personnel shall be laundered regularly. After contact with the product, all parts of the body that have been soiled must be washed.
Hygiene measures	Observe normal hygiene standards. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash hands after use.
Process conditions	Ensure that eye flushing systems and safety showers are located close by in the work place.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Blue.
Odour	No information available.
Odour threshold - lower	No information available as testing has not been completed.
Odour threshold - upper	No information available as testing has not been completed.
pH-Value, Conc. Solution	12.5 - 14.5
pH-Value, Diluted solution	Not applicable as the product is a concentrated solution.
Melting point	No information available as testing has not been completed.
Initial boiling point and boiling range	No information available as testing has not been completed.
Flash point	Technically not feasible.
Evaporation rate	No information available as testing has not been completed.
Flammability state	The product is not flammable.
Flammability limit - lower(%)	Not applicable as the product is not flammable.
Flammability limit - upper(%)	Not applicable as the product is not flammable.
Vapour pressure	No information available as testing has not been completed.
Vapour density (air=1)	No information available as testing has not been completed.
Relative density	1.034.
Bulk density	Not applicable as the product is a liquid.
Solubility	Soluble in water.
Decomposition temperature	No information available as testing has not been completed.
Partition coefficient; n-Octanol/Water	No information available as testing has not been completed.
Auto ignition temperature (°C)	Not applicable as the product is not flammable.
Viscosity	No information available as testing has not been completed.
Explosive properties	Not classified as explosive.
Oxidising properties	The product does not meet the criteria to be classified as oxidising.

9.2 Other information

Molecular weight	Not applicable as the product is a mixture.
Volatile organic compound	No information available as testing has not been completed.
Other information	None noted.

Section 10: Stability and reactivity

10.1 Reactivity

Reactivity	Reaction with: strong oxidising substances and acids.
------------	---

10.2 Chemical stability

Stability Stable under normal temperature conditions and recommended use.

10.3 Possibility of hazardous reactions

Hazardous reactions On contact with aluminium or light alloys hydrogen gas may be evolved. Reactions may occur with strong oxidizing materials and strong acids.

Hazardous polymerisation Will not polymerise.

Polymerisation description Not applicable.

10.4 Conditions to Avoid

Conditions to avoid Heat, sparks, open flames, temperature extremes and direct sunlight. Avoid storing in large quantities or for long periods of time.

10.5 Incompatible materials

Materials to avoid Do not mix with other chemicals unless listed on directions. Avoid contact with oxidising substances and acids.

10.6 Hazardous decomposition products

Hazardous decomposition products During fire, toxic gases (CO, CO₂) are formed. Nitrogen oxides (NO_x). Hydrogen cyanide (HCN).

Section 11: Toxicological information

11.1 Information on toxicological effects

Toxicological information No toxicological information for the overall finished product.

Acute toxicity (Oral LD50) No information available as testing has not been completed.

Acute toxicity (Dermal LD50) No information available as testing has not been completed.

Acute toxicity (Inhalation LD50) No information available as testing has not been completed.

Serious eye damage/irritation Causes severe eye damage.

Skin corrosion/irritation The product is classified as a skin corrosion/irritation hazard.

Respiratory sensitisation The product is not classified as a respiratory hazard.

Skin sensitisation The product is not classified as a skin sensitisation hazard.

Germ cell mutagenicity The product is not classified as a mutagen.

Carcinogenicity The product is not classified as a carcinogen hazard.

Specific target organ toxicity - Single exposure:

STOT - Single exposure The product is not classified as a single exposure specific target organ toxin.

Specific target organ toxicity - Repeated exposure:

STOT - Repeated exposure The product is not classified as a repeat exposure specific target organ toxin.

Inhalation No specific symptoms noted. Inhalation may cause respiratory irritation.

Ingestion May cause chemical burns in mouth and throat. May cause severe internal injury.

Skin contact Corrosive. Causes severe skin burns.

Eye contact Extreme irritation of eyes and mucous membranes, including burning and tearing. Corrosive to eyes.

Waste management When handling waste, consideration should be made to the safety precautions applying to handling of the product.

Routes of entry Eyes, skin, ingestion or inhalation.

Target organs Eyes, skin, digestive system, respiratory system.

Aspiration hazards: The product is not classified as an aspiration hazard.

Reproductive toxicity: The product is not classified as a reproductive hazard.

Name	LD50 oral	LD50 dermal	LD50 inhalation
disodium metasilicate	1153.00mg/kg Rat		

Section 12: Ecological information**12.1 Toxicity**

Acute toxicity - Fish	Alcohols, C12 -15, ethoxylated (CAS 68131-39-5) LC50: (96 hours) 0.59 mg/l, Pleuronectes platessa . REACH dossier information. SODIUM HYDROXIDE (CAS 1310-73-2) LC50: (96 hours) 45.4 mg/l, Oncorhynchus mykiss (Rainbow trout). IUCLID chemical data sheet.
Acute toxicity - Aquatic invertebrates	Alcohols, C12 -15, ethoxylated (CAS 68131-39-5) EC50: (48 hours) 0.14 mg/l, Daphnia magna. REACH dossier information. SODIUM HYDROXIDE (CAS 1310-73-2) EC50: (48 hours) 40.4 ug/L, Ceriodaphnia sp. REACH dossier information.
Acute toxicity - Aquatic plants	Alcohols, C12 -15, ethoxylated (CAS 68131-39-5) EC50: (72 hours) 0.75 mg/l, Selenastrum capricornutum. REACH dossier information.
Acute toxicity - Microorganisms	No information available as testing has not been completed.
Chronic toxicity - Fish	No information available as testing has not been completed.
Chronic toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Chronic toxicity - Aquatic plants	No information available as testing has not been completed.
Chronic toxicity - Microorganisms	No information available as testing has not been completed.
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic organisms.
Eco toxicological information	No ecological toxicity available on the overall finished product.

12.2 Persistence and degradability

Degradability	The degradability of the product has not been stated.
Biological oxygen demand	No information available as testing has not been completed.
Chemical oxygen demand	No information available as testing has not been completed.

12.3 Bioaccumulative potential

Bioaccumulative potential	No data available on bioaccumulation.
Bioaccumulation factor	No information available as testing has not been completed.
Partition coefficient; n-Octanol/Water	No information available as testing has not been completed.

12.4 Mobility in soil

Mobility	Soluble in water.
-----------------	-------------------

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment Product is not identified as PBT or vPvB.

12.6 Other adverse effects

Other adverse effects	None known.
------------------------------	-------------

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
disodium metasilicate	LC50 96 Hours 3185.00mg/l Pimephales promelas (Fat-head Minnow)	EC50 48 Hours 4857.00mg/l Daphnia magna	
N,N-dimethyltetradecylamine N-oxide	LC50 96 Hours 5.00mg/l Freshwater Fish		
propan-2-ol	LC50 96 Hours 9640.00mg/l Pimephales promelas (Fat-head Minnow)		

Section 13: Disposal considerations

Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product.
-------------------------	--

13.1 Waste treatment methods

Disposal methods	Dispose of waste and residues in accordance with local authority requirements. For waste
-------------------------	--

disposal, use a licensed industrial waste disposal agent.

Section 14: Transport information

14.1 UN number

UN no. (ADR)	UN1719
UN no. (IMDG)	UN1719
UN no. (IATA)	UN1719

14.2 UN proper shipping name

ADR proper shipping name	CAUSTIC ALKALI LIQUID, N.O.S. (disodium metasilicate + sodium hydroxide)
IMDG proper shipping name	CAUSTIC ALKALI LIQUID, N.O.S. (disodium metasilicate + sodium hydroxide)
IATA proper shipping name	CAUSTIC ALKALI LIQUID N.O.S. (disodium metasilicate + sodium hydroxide)

14.3 Transport hazard class(es)

ADR class	8
IMDG class	8
IATA class	8

Transport labels



14.4 Packing group

ADR/RID/ADN packing group	III
IMDG packing group	III
IATA packing group	III

14.5 Environmental hazards

ADR	No
IMDG	No
IATA	No

14.6 Special precautions for user

EMS	F-A, S-B
Emergency action code	A3
Hazard no. (ADR)	80
Tunnel restriction code	(E)

14.7 Transport in bulk according to annex II of MARPOL73/78 and the IBC code

Not applicable.

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 453/2010 of 20th May 2010 amending regulation (EC) No 1907/2006.
Approved code of practice	Workplace Exposure Limits Guidance Note EH40/2005. 2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)
Chemical safety assessment	No chemical safety assessment has been carried out.

Section 16: Other information

General information	This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.
Revision comments	This is a third issue. [3]Information updated. [5]Information updated. [8]Information updated. [9]Information updated. [11]Information updated. [12]Information updated. [15]Information updated.
Revision date	29 May 2020
Supersedes date	17 July 2017
Revision	3
Safety data sheet status	Approved.

Hazard statements in full

H314	Causes severe skin burns and eye damage.
H335	May cause respiratory irritation.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H302	Harmful if swallowed.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.